

Product	Adula 22	Diffuse 24
---------	----------	------------

ADULA 22

DIFFUSE 24

Apparecchio illuminante da soffitto/parete e da sospensione, 24Vdc, con emissione luminosa diffusa. Disponibile con modulo LED da 12W, 18W, 24W, 30W, temperatura colore 2700K, 3000K, 4000K e indice di resa cromatica CRI85 e CRI95.
A 24Vdc ceiling/wall or suspension luminaire, with diffused light emission. Available with 12W, 18W, 24W and 30W LED module, 2700K, 3000K and 4000K colour temperature and CRI85 and CRI95 (colour rendering index).

 IP20  

TECHNICAL DATA

Mounting	Ceiling/Wall Suspension
Dimensions (Ceiling/Wall)	H 46 mm x W 22 mm x L 600-900-1200-1500 mm
Dimensions (Suspension)	H 25 mm x W 22 mm x L 600-900-1200-1500 mm
Light source	SMD mid power LED technology
Power supply	24 Vdc
Control	Constant voltage driver to be ordered separately
Insulation class	III

Power	12 W (600 mm)			Power	24 W (1200 mm)		
CRI	85 95			CRI	85 95		
Colour temperature	2700 K	3000 K	4000 K	Colour temperature	2700 K	3000 K	4000 K
Source flux	1468 1221 lm	1500 1288 lm	1531 1314 lm	Source flux	2937 2443 lm	3000 2577 lm	3063 2628 lm
Luminous flux	954 793 lm	975 837 lm	995 854 lm	Luminous flux	1909 1587 lm	1950 1675 lm	1990 1708 lm
Luminous efficacy	79,5 66 lm/W	81,2 69,7 lm/W	82,9 71 lm/W	Luminous efficacy	79,5 66 lm/W	81,2 69,7 lm/W	82,9 71 lm/W

Power	18 W (900 mm)			Power	30 W (1500 mm)		
CRI	85 95			CRI	85 95		
Colour temperature	2700 K	3000 K	4000 K	Colour temperature	2700 K	3000 K	4000 K
Source flux	2202 1832 lm	2250 1932 lm	2297 1971 lm	Source flux	3671 3053 lm	3750 3221 lm	3829 3285 lm
Luminous flux	1431 1190 lm	1462 1255 lm	1493 1281 lm	Luminous flux	2386 1984 lm	2437 2093 lm	2488 2135 lm
Luminous efficacy	79,5 66 lm/W	81,2 69,7 lm/W	82,9 71 lm/W	Luminous efficacy	79,5 66 lm/W	81,2 69,7 lm/W	82,9 71 lm/W

MATERIALS

Body	Extruded aluminium
Finishing	Powder-coated, galvanic treatment
Screen	Opal extruded polycarbonate

FINISHING

light gold black nickel
rose gold titanium

CODE COMPOSITION

AD22 ____ 24 08 __ DI __

	Finishing	GC light gold GR rose gold NB black nickel TI titanium
	Colour temperature	27 2700K 30 3000K 40 4000K
	CRI	5 85 6 95
	Power	12W 600 mm 18W 900 mm 24W 1200 mm 30W 1500 mm
	Mounting	CW ceiling/wall S suspension

Example of code composition
AD22 CW 12W 24 08 6 30 DI GC

ACCESSORIES

LED Driver DALI
Cod. 28001663

Constant voltage 24 Vdc, rated power 60 W,
IP 20, dimensions: L 180 x W 43 x H 29,8 mm



LIGHT BEAMS

Light distribution diffuse

DIFFUSE

